


# Precision High Capacity Resistors

## Model 1282

Code:	1282 EN
Delivery:	ex stock/16 weeks
Warranty:	24 months



1282 EN

- Temperature coefficient  $\leq 20$  ppm/K
- Nominal load 20 W
- Ranges  $1 \text{ m}\Omega \dots 100 \text{ m}\Omega$
- Four-terminal measurement principle
- Accuracy 0.02 %
- For technical frequency 50 Hz

### Application

In connection with very precise digital voltmeters the model 1282 resistors are used as measuring resistors for accurate registration of direct and alternating currents up to 200 A. The compact construction supports universal application. The exceptional low temperature coefficient extends the scope of application a second time.

A typical application is the wide range of quality and reliability testing. Regular measurements give a reliable information of the quality level of parts, instruments and systems.

### Description

Technologies already approved with our precision and calibration resistors - which especially guarantee a secure conduction of the dissipation heat - have been transferred to the precision high capacity resistors. Those are designed on four-wire measurement principle. The voltage path is equalized to the customized value and to an accuracy of 0.02 %, (with reference temperature = 23 °C).

At maximum load a temperature increase within the resistor occurs. This temperature increase is compensated by a large surface area of the cooling body. The heat resistance of the resistors described is 1 K/W: The temperature of the resistor rises 1 K per Watt of supplied energy. All power and limiting values of the diagrams overleaf refer to the resistor material MANGANIN®. Unfavourable installation with insufficient possibility of ventilation and cooling have to be taken into consideration accordingly.

The potential tap is effected via brass terminals with 4 mm hole. The screw-terminals for the current feed are dimensioned according to the maximum capacity.

## Technical Data

Resistance ranges:	1 mΩ ... 100 mΩ, any resistance value within this range is available
Resistance tolerance:	0.02 %
Calibration temperature:	23 °C
Resistance material:	MANGANIN®
Temperature coefficient:	< 20 ppm/K
Temperature dependence:	$R_t = R_{20} (1 + a_{20} (t - 20) + b (t - 20)^2)$ $a_{20} = 0 \dots 20 \cdot 10^{-6}$ $b = -0.59 \cdot 10^{-6}$
Long-term stability:	< 0.01 % over years
Long-term load:	20 W
Short-time over load:	approx. 90 W < 1 min
Ultimate load:	60 W at 25 °C environmental temperature
Current limit (at 1 mΩ):	200 A
Surface temperature:	max. 85 °C, results from heat resistance + ambient temperature
Thermal resistance:	1 K/W

### Construction:

Resistance element is made of a MANGANIN® sheet with four terminal connection. It is installed free of mechanical tension between two cooling bodies, current junction is realized via screw terminals, potential tap is made via brass terminals.

Capacity $C_R$ :	< 4 nF, resistance element to cooling body
Electrical strength:	test voltage 1950 VDC
Max. potential:	42 V against cooling body insulated mounting required for higher voltages
Isolation resistance $R_{is}$ :	100 MΩ, cooling body against resistance element
Specifications:	according DIN EN 60477
Dimensions (W x H x D):	265 x 100 x 150 [mm]
Weight:	ca. 2.3 kg

## Order Information

Precision high capacity resistors

Resistance value 1 mΩ

Resistance value 10 mΩ

Resistance value 100 mΩ

Any value in the range 1 ... 100 mΩ

Delivery: 12 weeks

**Model 1282-0.001**

**Model 1282-0.01**

**Model 1282-0.1**

**Model 1282S**

DAkkS Calibration Certificate for model 1282 **12DKD-1282**

Manufacturer calibration certificate for model 1282 **12WKS-1282**

## DAkkS Calibration Certificate


The calibration laboratory D-K-15141-01-00 at burster praezisionsmesstechnik is supervised by DAkkS (Deutsche Akkreditierungsstelle GmbH) according to ISO 17025. It can prove its status by a certificate and is authorized to issue calibration certificates with the DAkkS logo and with the DKD logo (Deutscher Kalibrierdienst). These calibration certificates are internationally approved by multilateral contracts.

Precision high capacity resistors series 1282 can be delivered with a DAkkS calibration certificate. The calibration is made with max. 10 A<sub>DC</sub> AT 23° C.


## Manufacturer Calibration Certificate

The high capacity resistors can also be delivered with a manufacturer calibration certificate. It confirms the traceability of the used secondary voltage and resistance standards to the national standards as well as the logging of the measured value and its uncertainty.

## Load limit curve




## Load reduction curve



The max. load capacity with different ambient temperature as a function of the warm-up error can be taken from the load reduction curve. **Example:** Ambient temperature: max. 50°C; accepted ΔR by temperature influence: max. 0.02 %; max. permissible load: 10 W.

## Characteristic load as a function of excessive temperature



Cooling body temperature = ambient temperature + excessive temperature.

$P_{tot}$  = dissipation power  
 $t_u$  = ambient temperature  
 $\Delta t$  = temperature elevation over ambient temperature

